



# WALLMOUNT INDOOR LITHIUM BATTERY

The WallMount Indoor 280Ah batteries are ideal for low-voltage residential indoor energy storage applications. The batteries use lithium iron phosphate cells with the highest safety performance and an intelligent Battery Management System (BMS) that can monitor and record the voltage of each cell along with the current, voltage, and temperature of the module in real-time. The BMS also contains a passive balance function and an advanced battery control method, both of which improve the performance of the battery pack.

**BUILT-IN  
200A BMS**

**INTEGRATED  
600A BUSBARS**

**82.6MWh  
LIFETIME  
PRODUCTION\***

**10 YEAR  
WARRANTY  
>8000 CYCLES @  
80% DOD**

## ON-BOARD LCD TOUCH SCREEN

Easy to see BMS monitoring, and selectable closed-loop communications with EG4, Schneider, Sol-Ark, Victron, Growatt, Megarevo, Luxpower, and Deye inverters.

## DUAL ON-BOARD FIRE ARRESTORS

Offer fail-safe protection against thermal runaway.

## INTEGRATED SELF-HEATING FEATURE

Internal heating keeps cells operating during cold temperatures.

## INTEGRATED BUSBARS

The battery design comes manufactured with 600A internal busbars with multiple terminals (4 positive & 4 negative) eliminating the need for external busbars when paralleling batteries and/or multiple inverters.

## INNOVATIVE EMERGENCY STOP FUNCTION

The optional ESS disconnect can shut down all batteries and inverters (if equipped with rapid shut down capability) with the press of a button.

## THE PERFECT PARTNER TO EG4 INVERTERS

The optional conduit box mates up directly to the connection ports of EG4 inverters allowing a sleek and efficient installation. For other inverters or stand-alone battery installation, the conduit box plugs should be installed.

SCAN FOR UPDATED  
DOCUMENTS



## SPECIFICATION SHEET

MODULE OPERATING PARAMETERS			
PARAMETER	BMS	Recommended Setting	
VOLTAGE	51.2V	-	
CAPACITY	280Ah	-	
CHARGING VOLTAGE (BULK/ABSORB)	56.0V (+/-0.8V)	56.2V (+/-0.2V)	
FLOAT	-	54V (+/-0.2V)	
LOW DC CUTOFF	44.8V	47-45.6V (start high, lower as needed)	
CHARGING CURRENT	200A (Max. continuous)	60A - 160A	
DISCHARGING CURRENT	200A (Max. continuous)	160A	
ENVIRONMENTAL PARAMETERS			
CHARGING RANGE	32° to ≈113°F (0°C to ≈45°C)		
DISCHARGING RANGE	-4°F to ≈122°F (-20°C to ≈50°C)		
STORAGE RANGE	-4°F to ≈122°F (-20°C to ≈50°C)		
INGRESS PROTECTION	IP20		
CHARGING/ DISCHARGING PARAMETERS			
CHARGE	Spec	Delay	Recovery
CELL VOLTAGE PROTECTION	3.8V	1 sec	3.45V
MODULE VOLTAGE PROTECTION	60.0V	1 sec	55.2V
OVER CHARGING CURRENT 1	>205A	10 sec	-
OVER CHARGING CURRENT 2	>225A	3 sec	-
TEMPERATURE PROTECTION	<23°F or >158°F <-5°C or >70°C	1 sec	>32°F or <140°F >0°C or <60°C
DISCHARGE	Spec	Delay	Recovery
CELL VOLTAGE PROTECTION	2.3V	1 sec	3.1V
MODULE VOLTAGE PROTECTION	44.8V	1 sec	48V
OVER-CHARGING CURRENT 1	>205A	10 sec	60 sec
OVER-CHARGING CURRENT 2	>300A	3 sec	60 sec
SHORT CIRCUIT	>600A	<0.1 mS	-
TEMPERATURE PROTECTION	<-4°F or >167°F <-20°C or >75°C	1 sec	>14°F or <149°F >-10°C or <65°C
PCB TEMP PROTECTION	>230°F (>110°C)	1 sec	@ <176°F (<80°C)
GENERAL SPECIFICATIONS			
PARAMETER	Spec		Condition
CELL BALANCE	120mA	Passive Balance	Cell Voltage Difference >40mV
TEMPERATURE ACCURACY	3%	Cycle Measurement	Measuring Range -40°F to ≈212°F (-40°C to ≈100°C)
VOLTAGE ACCURACY	0.5%	Cycle Measurement	For Cells & Module
CURRENT ACCURACY	3%	Cycle Measurement	Measuring Range -200A - 200A
SOC	5%	-	Integral Calculation
POWER CONSUMPTION	Sleep & Off Mode	<300uA	Storage/Transport/Standby
POWER CONSUMPTION	Operating Mode	<25mA	Charging/Discharging
COMMUNICATION PORTS	RS485/CAN		Can be customized
BATTERY HEATER SPECIFICATIONS			
PARAMETER	Spec		Condition
VOLTAGE	56V		-
POWER CONSUMPTION	224W		-
INTERNAL BATTERY TEMPERATURE	≤32°F (0°C)/≥41°F (5°C)		Heat On/Heat Off

## PHYSICAL SPECIFICATIONS

DIMENSIONS (H×W×D) 36.4 in.×18.1 in.×9.6 in. (925 mm×460 mm×245 mm)

WEIGHT 282.2 lbs. (128 kg)

DESIGN LIFE >15 Years

CYCLE LIFE >8000 Cycles, 0.5C 80% DOD

LIFETIME PRODUCTION 82.6MWh\*

## SAFETY CERTIFICATIONS

CERTIFICATIONS UL1973, UL 9540A (Testing)

*\*(51.2V×280Ah/1000×80%×8000 cycles/1000)90%=MWh*